



Industrial scales

Processing and control scales - Zenith





FICHE TECHNIQUE

	S29	MKW	SKW
Payloads	6 kg/1 gr - 15 kg/2 gr	60 Kg/10 gr	30 Kg/10 gr
Weighing tray	Stainless steel 320 x 190 mm	Stainless steel 420 mm x 520 mm	Stainless steel 350 mm x 450 mm
Weight measurement	Load cell	IP 65 load cell (OIML C3)	IP 65 load cell (OIML C3)
Display	Backlit LCD display with large digits	24 mm backlit display	24 mm backlit display
Keyboard	-	7-key	7-key
Internal resolution	-	500,000 points	500,000 points
Batteries	Built-in rechargeable battery (70 h runtime)	Built-in rechargeable battery (70 h runtime)	Built-in rechargeable battery (70 h runtime)
Tare	Tare reset function	-	-
Temperature limits	-	-10° / + 40° C	-10° / + 40° C
Power supply	12V/500mA ; battery 6V/3,2 Ah	230 Vac / 9 Vcc 500 mA	230 Vac / 9 Vcc 500 mA
Dimensions	243 x 300 x 127 mm	-	-
Accessories	-	Painted trolley 420 mm x 520 mm Inox trolley 420 mm x 520 mm	

MODÈLES



9E0KN720000001
SCALE S29 6 KG/1 GR

9E0KN720000002
SCALE S29 15 KG/2 GR

9E0KN500000006
PLATFORM SCALE SKW 30 KG/10 GR

9E0KN500000008
PLATFORM SCALE MKW 60 KG/10 GR

Professional floor scale

Professional floor scale, made of stainless steel and equipped with high precision load cells with high rigidity, wide steel base, task trolleys and impoised scale not approved for trade. Available levels: 5 kg/2 gr and 6 kg/1 gr. 15 kg/2 gr and 30 kg/10 gr. Water resistant; IP 65 degree of protection. Functions: piece counting, check weighing, weight accumulation, tare, auto zero, auto power off, auto shut down. Totalization. For indoor use, approvable for trade.

- Stainless-steel weighing plate
- 60kg and 30kg capacity models available

Via I. Newton, 4 - 43010 Fontevivo PR - NUMÉRO DE TVA : IT02498250345 - TÉL : +39 0521 680111 - FAX : - CODE UNIVOQUE: 7K4AJ54

Les données techniques de ce site ne sont pas contraignantes et peuvent être modifiées sans préavis.

Dernière mise à jour : 28 septembre 2026