



K3 LINERFREE

K3 LINERFREE

400mm K3 LINERFREE



- ??
- ??
  - ???????
  - 400mm/?
  - ????
  - ???????
  - POS
  - RS232/USB/
  - QRCODE DATAMATRIX PDF417 AZTEC
  - TrueFont
  - 58 60 80mm
  - 100mm

????

-

????

|                       |                                                                                                                                                                                  |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Printing Method       | Thermal printing                                                                                                                                                                 |
| Number of dots        | 8 dots / mm                                                                                                                                                                      |
| Resolution            | 203 dpi                                                                                                                                                                          |
| Printing (mm/sec)     | 400 mm/s                                                                                                                                                                         |
| Auto-cuter            | Cutter life 1 million cuts<br>Total and partial cut                                                                                                                              |
| Character set         | Standard font, Chinese 18030, Russian font                                                                                                                                       |
| Numbers of columns    | 32      42      56                                                                                                                                                               |
| Characters            | 2.25 x 3   1.625 x 3   1.25 x 3 (L x H mm)-Normal                                                                                                                                |
| Supported Barcode     | UPCA, UPCE, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QRCODE, DATAMATRIX, PDF417, AZTEC                                                                        |
| Paper width           | 58mm / 60mm / 80mm                                                                                                                                                               |
| Paper weight          | from 55 to 90 gr/m <sup>2</sup>                                                                                                                                                  |
| Roll Dimension        | max Ø 100 mm                                                                                                                                                                     |
| Sensors               | Head temperature<br>Paper presence<br>Black mark detection<br>Cover open<br>Low paper                                                                                            |
| Emulation             | CUSTOM/POS                                                                                                                                                                       |
| Interfaces            | RS232 / USB (or Virtual COM) / ETHERNET<br>Cash Drawer                                                                                                                           |
| Flash Memory          | 4MB Flash SPI + 1MB internal to the micro                                                                                                                                        |
| RAM Memory            | 64 MB                                                                                                                                                                            |
| Data Buffer           | 16 kB                                                                                                                                                                            |
| Drivers               | Windows® (32/64 bit) – only on request WHQL and silent installation;<br>Linux (32/64 bit);<br>Virtual COM (Linux or Windows 32/64 bit);<br>OPOS;<br>JavaPOS;<br>Android™;<br>iOS |
| Software Tools        | PrinterSet; Virtual COM; Custom Power Tool, Custom Windows API                                                                                                                   |
| Power supply          | 24 Vdc                                                                                                                                                                           |
| Head Life             | 200 Km                                                                                                                                                                           |
| Operating temperature | 0°C + 40°C                                                                                                                                                                       |
| Dimensions            | 206 mm (L) × 148 mm (W) × 140mm (H)                                                                                                                                              |
| Weight                | 1.98 Kg                                                                                                                                                                          |

??



**911HM011200733**  
PRINTER K3 HIGH SPEED  
LINERFREE ETH USB RS232

Via I. Newton, 4 - 43010 Fontevivo PR - IT02498250345 - +39 0521 680111 - - 7K4AJ54  
28 2026