



TK202III

TK202III	> 200 / .	20 82.5	80 255 /m ² . 1D 2D .
----------	-----------	---------	----------------------------------



??

- ; 200 /
- 20 82.5
- : 70 255 / ²
- ;
- /
- 2

???

- 1D 2D : UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, PDF417, DATAMATRIX, QRCODE
- RS232 + USB
- :
- ; ,
- : (2MB)
- : True Font ,

??

????????

- AC 40mm USB 220V

????

????

8 /	
203 dpi	
/	>200 /
PC437, PC850. PC860. PC863, PC865, PC858	
1 8	
, 90°, 180°, 270°	
20	82.5 (2)
70	255 / ²
CUSTOM/POS - SVELTA	
RS232 / USB	
64 KB	
16 MB	
(2MB)	
Windows® 32/64 --- WHQL	
Linux 32/64	
COM Linux Windows 32/64	
OPOS;	
™	
iOS	
PrinterSet, CustomPowerTool, Status Monitor	
24 Vac ± 10%	
0.8A (12,5%)	
100 /100M	
252,1 (L) x 192,6 (H) x 216 (W)	
4	

??



911BD050100313
PRINTER TK202III USB RS232